



Example image

APPLICATION PURPOSES

- For drainage of floor-even showers
- For installation in the room or on the wall
- For installation in thin bed mortar
- For composite seals
- Suitable for less-abled installation

CHARACTERISTICS

- Quality-monitored in accordance with EN 1253-3
- With integrated slope
- Shower channel can be cut to length
- Suitable for tile structures on floor from 10–35 mm
- Shower channel can be aligned in height, inclination and offset

- Easy cleaning
- Water drainage above the composite seal
- Water drainage above the finished floor when using the sleeve
- Load-bearing capacity, class K 3 (3 kN)
- With anti-fingerprint coating

TECHNICAL DATA

Product material CrNiMo steel 1.4404 (EN 10088)

SCOPE OF DELIVERY

- Comb insert
- Inlet connection piece with compensation ring
- Suction cup

- Sleeve

TO ORDER ADDITIONALLY

- Installation set for shower channels of the CleanLine series
- Geberit installation set for CleanLine shower channel, for screed height at inlet 90–220 mm
- Geberit installation set for CleanLine shower channels, floor-penetrating installation
- Geberit installation set for CleanLine shower channel, for screed height at inlet 65–90 mm

INFO

- Natural stone tiles in the shower area may discolour

Art. no.	Colour / surface	L cm	B cm	H cm
154.440.KS.1	Frame: Stainless steel polished Surface: Atainless steel brushed	30–90	4.4	1

<i>Art. no.</i>	<i>Colour / surface</i>	<i>L cm</i>	<i>B cm</i>	<i>H cm</i>
154.440.QC.1	Frame, Surface: black chrome / Brushed	30-90	4.4	1
154.440.39.1	Frame: champagne / Polished Surface: champagne / Aainless steel brushed	30-90	4.4	1
154.441.KS.1	Frame: Polished Surface: Aainless steel brushed	30-130	4.4	1
154.441.QC.1	Frame, Surface: black chrome / Brushed	30-130	4.4	1
154.441.39.1	Frame: champagne / Polished Surface: champagne / Aainless steel brushed	30-130	4.4	1