Geberit Delta concealed cistern 12 cm, 6 / 3 litres, with front actuation

R1/2

235 ¥ 44⁵

↓ 10⁵

135


≥ 30 ◀

100 ▽ 84⁵

365

GEBERIT






APPLICATION PURPOSES

- For masonry walls
- For installation in part or room-height prewall installations
- For installation in room-height installation walls
- For floor-standing and wall-hung WCs
- · For single flush, dual flush or stop-and-go flush

CHARACTERISTICS

- · Concealed cistern with front actuation
- · Concealed cistern, fully insulated against condensation
- · Immediate post flush possible with factory setting
- Flush bend fitted
- Water supply connection on the rear or top centre



· Connection hose on angle stop valve can be attached without tools

TECHNICAL DATA

|–1–6 100

Flow pressure	0.1–10 bar
Flush volume, factory setting	6/31
Flush volume large, adjustment	4 / 4.5 / 6 / 7.5 l
range	
Flush volume small, adjustment	2–4
range	
Product material	Plastic

SCOPE OF DELIVERY

- Water supply connection unit R 1/2", compatible with MasterFix and MeplaFix, with integrated angle stop valve and adapter ring
- Protection box for service opening
- 2 distance bolts
- Flush bend with recess shells
- Protection plug
- 2 slotted flat irons
- 2 fixing brackets
 - · Fastening material

INFO

· Actuator plate has to be ordered separately