



# Geberit KombifixBasic element for wall-hung WC, 108 cm, with Delta concealed cistern 12 cm



## APPLICATION PURPOSES

- For masonry walls
- For installation in part or room-height prewall installations
- For wall-hung WCs with connection dimensions in accordance with EN 33:2011
- For single flush, dual flush or stop-and-go flush

## CHARACTERISTICS

- Zinc-plated mounting frame
- Mounting frame with four fastening brackets
- Fastening for connection bend can be mounted without tools from front
- Concealed cistern with front actuation
- Concealed cistern, fully insulated against condensation
- Immediate post flush possible with factory setting
- Water supply connection on the rear or top centre
- Connection hose on angle stop valve can be attached without tools

- With conduit pipe for feed pipe for Geberit AquaClean shower toilets and for connection cable
- Fastening option for electrical connection

## TECHNICAL DATA

Flow pressure	0.1–10 bar
Flush volume, factory setting	6 / 3 l
Flush volume large, adjustment range	4 / 4.5 / 6 / 7.5 l
Flush volume small, adjustment range	2–4 l
Flow rate at 3 bar	0.16 l/s
Product material	Steel
Height-adjustable	No

## SCOPE OF DELIVERY

- Water supply connection unit R 1/2", compatible with MasterFix and MeplaFix, with integrated angle stop valve and adapter ring

- Protection box for service opening
- 2 distance bolts
- Connection bend 90° made of PE-HD, ø 90 mm
- Adapter socket made of PE-HD, ø 90 / 110 mm
- Connection set for WC, ø 90 mm
- 2 protection plugs
- 2 threaded rods M12
- Fastening material

## ACCESSORIES

- Geberit Kombifix set of leg supports
- Geberit Kombifix set of studs with foot plate

## INFO

- Actuator plate has to be ordered separately

Art. no.	B cm	H cm	T cm
110.100.00.1	42	108	12