

Geberit Duofix element for wall-hung WC, 82 cm, with Omega concealed cistern 12 cm









APPLICATION PURPOSES

- · For drywall construction
- · For installation in part-height prewall installations
- For wall-hung WCs with connection dimensions in accordance with EN 33:2011
- For wall-hung WCs with projection up to 62 cm
- For dual flush
- For floor constructions 0–20 cm

CHARACTERISTICS

- Statically self-supporting frame, protected against corrosion with powder coating
- Frame with ø 9 mm drilling holes for fastening in wood frame construction
- Frame prepared for support brackets for WC ceramic appliances with small contact surfaces
- · Galvanized feet
- Feet adjustable 0-20 cm
- · Non-slip leg supports
- Rotatable foot plates
- Foot plate depth suitable for installation in U-profiles UW 50 and UW75 and Geberit Duofix system rails
- Connection bend can be mounted without tools at different depths, adjustable range 45 mm

- · Fastening for connection bend, sound-absorbing
- · Concealed cistern with top or front actuation
- Concealed cistern, fully insulated against condensation
- · Immediate post flush possible with factory setting
- Tool-free installation and maintenance work on concealed cistern
- Water supply connection on the left or rear left
- Protection box for service opening can be cut to length
- With conduit pipe for feed pipe for Geberit AquaClean shower toilets and for connection cable
- · Fastening option for electrical connection
- Power & Connect Box mountable

TECHNICAL DATA

Flow pressure	0.1–10 bar
Flush volume, factory setting	6/31
Flush volume large, adjustment	4/4.5/6/7.51
range	
Flush volume small, adjustment	2–4 l
range	
Flow rate at 3 bar	0.16 l/s
Height-adjustable	No

SCOPE OF DELIVERY

- Water supply connection R 1/2", compatible with MasterFix and MeplaFix, with integrated angle stop valve and hand wheel
- Protection box for service opening
- Connection set for WC, ø 90 mm
- Connection bend 90° made of PE-HD, ø 90 mm
- Adapter socket made of PE-HD, ø 90 / 110 mm
- · 2 protection plugs
- 2 threaded rods M12
- · Fastening material

ACCESSORIES

- Geberit set of Power & Connect box and power supply unit for element for wall-hung WC
- Geberit set of support brackets for WC ceramic appliances with small contact surfaces
- Geberit Duofix set of wall anchors for single installation, corner construction
- Geberit Duofix set of wall anchors for single installation
- Geberit Duofix set of wall anchors for single and system installation

INFO

· Actuator plate has to be ordered separately



Ar. no.	49 &	* &	~ &					
111.003.00.1	50	82	14					