

Model: LINKFLOOR TOWN CAMEL

Codes: 100350351

Group: G-222

Format: 22,8X180X0,55CM



	Size	Material	Type of material
Layer 1	0.5	Wear layer	Use layer with PU protection
Layer 2	0.1	Vinyl	
Layer 3	3.9	SPC	SPC core
Layer 4	1.0	IXPE	Foam

COMPOSITION

FEATURES

Imitates the surface of wood

Water and moisture resistant flooring, suitable for wet areas such as bathrooms and kitchens for residential use, provided the product's installation instructions are followed.

5 year warranty for commercial use valid for vinyl materials that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with ISO 10582.

Floor capable of dissipating excess electrical charges and distribute them over its entire surface

There are consistent color changes between pieces.

Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.

25 year warranty for domestic use valid for vinyl materials that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with ISO 10582.

Is suitable for installing on water radiant heating

Safety and joint durability are the main features of this easy installation system that guarantees the elimination of gaps between boards throughout the floor's lifetime. The pressure exerted between boards reinforces the union and prevents it from being carried out incorrectly.



LABORATORY TESTS		
Commercial area class	33	EN 10582**
Slip resistance (r)	R10	EN 16165 Anexo B*
Resistance to microscratching	MSR-A1/MSR-B1	EN 16094*
Formaldehyde emissions	E1	EN 717-2*
Slip resistance (pendulum-wet)	CL 2 (38)	EN 16165 Anexo C*
Tensile strength of joints	6.56 kN/m	ISO 24334*
Fire resistance	Bfl-s1	EN 14041:2004 AC:2006*
Fire resistance	CLASS A	ASTM E84*
Evaluation of propensity to accumulation of electrostatic charges	1.13 KV	EN 1815*
Heat resistance	0.049 M2*K/W	EN 12664*
Thermal conductivity	0.113 W/M*K	EN 12664*
Acoustic insulation	(8''): IIC=57 dB;STC=52dB	ASTM E492 ; ASTM E90*
Dynamic coefficient of friction	0.49	ANSI 137.1*
Smoke density (burning)	SDI: 400	ASTM E84*
Private area class	23	EN 10582**
Slip resistance (pendulum-dry)	86	EN 16165 Anexo C*

PACKING		
Sales units per box	2.052 M2/BOX	
Sales units per pallet	106.704 M2/PAL	
Sales units per unit	0.4104 M2/PIECE	
Sale unit	M2	
Base unit	ST	
Sales units per square meter	1 M2	
Net weight	10.221735 KG/M2	
Gross weight	10.677388 KG/M2	

SPECIAL PIECES									
SAP	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight
100354778	MAMPER LINKFLOOR TOWN CAMEL 7X120	G-163	2 PIECES/BOX	200 PIECES/PAL	11.9 PIECES/M2	-	-	1.58 KG/PIECES	1.64 KG/PIECES
100257147	PERFIL ADH LINKFLOOR ALUMINIO 3,5X270	G-121	40 PIECES/BOX	1000 PIECES/PAL	10.58 PIECES/M2	-	-	0.37 KG/PIECES	0.39 KG/PIECES
100354774	PERFIL ADH LINKFLOOR TOWN CAMEL 3,5	G-155	20 PIECES/BOX	1000 PIECES/PAL	9.26 PIECES/M2	-	-	0.77 KG/PIECES	0.8 KG/PIECES
100354770	ZOCALO LINKFLOOR PVC TOWN CAMEL 8X223	G-113	12 PIECES/BOX	648 PIECES/PAL	5.61 PIECES/M2	-	-	1.1 KG/PIECES	1.25 KG/PIECES
100343146	ZOCALO PVC PAPEL BLANCO 8X223X1,5	G-113	12 PIECES/BOX	648 PIECES/PAL	5.61 PIECES/M2	-	-	1.41 KG/PIECES	1.49 KG/PIECES

